

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/337759033>

# EVALUATION OF SOME TECHNICAL INDICATORS OF THE LOCALLY MODIFIED SHELLER FOR CORN GRAIN

Research · December 2019

CITATIONS

0

READS

5

3 authors, including:



**Firas Taha**

Al-Furat Al-Awsat Technical University

8 PUBLICATIONS 4 CITATIONS

[SEE PROFILE](#)



**Omar Rashid**

Al-Furat Al-Awsat Technical University

4 PUBLICATIONS 0 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:



أداء المحرّات الحفّار تحت أعماق حرّاة وسرع الجرّار [View project](#)



Academic Lecturers vs Researches [View project](#)

# EVALUATION OF SOME TECHNICAL INDICATORS OF THE LOCALLY MODIFIED SHELTER FOR CORN GRAIN

F. J. Taha  
Lecturer

A. H.U. Al-Khafajie  
Lecturer

O. M. Rashid  
Assist. lecturer

Dept. of Technicians Agricultural Machinery & Equipments  
Technical College / Al-musayyib – Al-Furat Al-Awsat Technical University

[Alsaady2011@yahoo.com](mailto:Alsaady2011@yahoo.com)

## ABSTRACT:

This study was carried out during 2017, in factory of shelling corn grains at Al-musayyib / Babylon governorate. The objective of this study evaluation some technical indicators of the locally modified sheller for corn grain by using sheller machine locally modified with different peripheral speed of shelling cylinder 900, 1100 and 1300 m/min, different clearance between shelling cylinder and concave 23 and 28 mm on the properties which were sheller productivity, quality productivity, power consumption and unshelled grains. This research was done by applying the split plot design experiment within RCBD using four. The results showed the following: clearance between shelling cylinder and concave 28 mm indicated significant superiority up on the clearance between shelling cylinder and concave 23 mm with highest sheller productivity (2.474 ton/h) and quality (193.735 kg.h/kw), while the clearance between shelling cylinder and concave 23 mm had lower power consumption 11.62 kw and lower percentage of unshelled grains 2.53 %; As increasing in the peripheral speed of shelling cylinder from 900 to 1100 and 1300 m/min increased the sheller productivity, quality and power consumption. The peripheral speed of shelling cylinder (1300 m/min) indicated significant superiority up on the peripheral speed of shelling cylinder 900 and 1100 m/min in achieving higher sheller productivity 3.039 ton/h and higher quality productivity 205.061 kg.h/kw. while the peripheral speed of shelling cylinder 900 m/min achieving lower power consumption 11.78 kw and lower percentage of unshelled grains 2.37 %.

Keywords: Locally modified sheller, Sheller machine, Sheller productivity, Shelling cylinder.

تقييم بعض المؤشرات الفنية لمفرطة حبوب الذرة المحورة محليا"

فراس جمعة طه احمد حمزة عمران الخفاجي عمر محسن رشيد

مدرس مدرس مدرس

قسم تقنيات هندسة الماكائن والمعدات الزراعية ,الكلية التقنية /المسيب – جامعة الفرات الأوسط التقنية

[Alsaady2011@yahoo.com](mailto:Alsaady2011@yahoo.com)

## المستخلص:

أجريت الدراسة بتاريخ 2017 , في معمل تفريط الذرة الصفراء في منطقة المسيب / محافظة بابل. كما أن هدف البحث دراسة تأثير استعمال ماكينة تفريط الذرة المحورة محليا" وبسرعة محيطية مختلفة لأسطوانة التفريط 900 , 1100 و 1300 م/دقيقة وأستخدمت خلوصات مختلفة بين أسطوانة التفريط والمقعر 23 و 28 ملم على المؤشرات الفنية التي تضمنت: إنتاجية المفرطة , الإنتاجية النوعية , القدرة المستهلكة و الحبوب غير المفرطة. طبق البحث باستعمال تصميم الألواح المنشقة وفق تصميم القطاعات العشوائية الكاملة وبأربع مكررات حيث أنه تم تحليل النتائج احصائيا" وأعطت النتائج التالية: تفوق الخلوص بين أسطوانة التفريط والمقعر 28 ملم على الخلوص بين أسطوانة التفريط والمقعر 23 ملم في تحقيق أعلى إنتاجية للمفرطة 2.474 طن/ساعة وأعلى إنتاجية نوعية بلغت 193.735 كغم . ساعة/كيلوواط , بينما أعطى الخلوص بين أسطوانة التفريط والمقعر 23 ملم في تحقيق أقل مقدار للقدرة المستهلكة 11.62 كيلوواط وأقل نسبة للحبوب غير مفرطة 2.53 % , الزيادة في السرعة المحيطية لأسطوانة التفريط من 900 الى 1100 ثم الى 1300 م/دقيقة. أدت الى الزيادة في الإنتاجية والإنتاجية النوعية والقدرة المستهلكة. تفوقت السرعة المحيطية لأسطوانة التفريط 1300 م/دقيقة على السرعة المحيطية لأسطوانة التفريط 900 و 1100 م/دقيقة في تحقيق أعلى إنتاجية للمفرطة 3.039 طن/ساعة وأعلى إنتاجية نوعية 205.061 كغم.ساعة/كيلوواط , بينما السرعة المحيطية لأسطوانة التفريط 900 حققت أقل قدرة مستهلكة 11.78 كيلوواط وأقل نسبة للحبوب الغير مفرطة 2.37 %.

كلمات مفتاحية: المفرطة المحورة محليا" , الماكينة المفرطة , إنتاجية المفرطة , أسطوانة التفريط.

## INTRODUCTION:

The maize crop is considered one of the pillars of the national economy because it's a strategic crop of economic importance, wide spread and ranks third after wheat and rice crops. Some researchers they conclude that the difference peripheral speed of shelling cylinder with the effect of concave it was main role for sheller productivity that reported by (1,6). the number of shelling factories [13] in different regions of Iraq governorates they have a prominent role in shelling and drying of corn grains this is confirmed by other researchers (7). It was considered the process of shelling one of the important processes which is the process of separating the grains from ears taking into consideration the moisture of the grain when shelling should not increase 25% so that the efficiency of shelling weak with an increase in the amount of damaged grain, consequently, productivity is low this is confirmed by some researchers (11). In order to get better performance for sheller should regulate the relationship between shelling cylinder and the clearance cylinder and concave this is consistent with what has been showed (13). The researchers (14) showed that many studies have been conducted to improve the work of sheller by increasing shelling productivity, shelling efficiency and quality of product through installation baffles and rasps in the shelling cylinder. The researcher (16) showed that the advantage from grains maize crop used 40% as feed for poultry and livestock in addition to that there are more food products is extracted from corn grains such as starch, oil and bread, Therefore, the increase in the production of maize grain has been directed through development and improvement machineries of shelling for grains. An expansion in the establishment the special factories of shelling for corn grains in agricultural areas characterized by their productivity of maize crop (17). The peripheral velocity of the feeder a proportional relationship with peripheral speed of shelling cylinder this is consistent with what has been pointed out by different researchers (18).

## MATERIALS AND METHODS OF WORK:

The experiment was carried out in factory of shelling corn grain in Al-musayyib Affiliated to the ministry of Agriculture at 2017, the grain

was shelled at a moisture of 16%, the research conducted by using the split plot design within (RCBD) with four replications to studying two factors:

- 1- **peripheral speed of shelling cylinder:** which included speeds of 900, 1100 and 1300 m/min, this was done through a cylinder with a diameter of 150 mm and a length of 950 mm and installed on it plates shaped radially with 6 panels and a distance 25 mm between a plate and another. The speed is controlled by electric motor (Leroy Somer), which is characterized by (three phase - variable speed) and power 20 hp.
- 2- **clearance between shelling cylinder and concave:** which included 23 and 28 mm used for this type slotted grate concave with a length 970 mm manufactured from AISI 1045 steel).

## INDICATORS STUDIED:

1- **Sheller productivity:** this is done through weighing bags collected at a certain time according to the following equation:

$$P_s = \frac{W_o}{T} * \frac{60}{1000} \dots \left( \frac{\text{ton}}{\text{h}} \right) \quad (8, 15)$$

$P_s$ -Sheller productivity, (kg/h)

$W_o$  -Weight output, (kg)

$T$ -Time, (min)

2- **Quality productivity:** this is calculated according to the following equation:

$$P_Q = \frac{P_s}{P_w} \dots \left( \frac{\text{kg} \cdot \text{h}}{\text{kw}} \right) \quad (2)$$

$P_Q$  - Quality productivity, (kg. h)

$P_s$  - Power consumption, (kw)

3- **Power consumption:** the power consumption was calculated by using device (Clamp meter), Chinese-made done by that device calculated the current and voltage values for electric motor, the power consumption was calculated from the following equation (19):

$$P_w = \frac{\sqrt{3}}{1000} * V * I * \cos \theta * E_{ff} \dots (kw)$$

$P_w$  - Power consumption, (kw)

$V$  - Voltage, (Volt)

$I$  - Current, (Ampere)

$\cos \theta$  - The angle between the current and voltage

$E_{ff}$  - Motor efficiency %

**4-Percentage of unshelled grains:** this was calculated by taking different samples of bags which were collected and then detach unshelled grain from cobs manually. Then the grain was weighed and calculating the percentage of unshelled grain from the following equation:

$$U_g = \frac{W_{un}}{W_o} * 100 \quad (\%) \quad (3)$$

$U_g$  – Percentage of unshelled grain, (%)

$W_{un}$  – Unshelled grain, (kg)

$W_o$  – Weight output, (kg)

## RESULTS AND DISCUSSION:

The table (1) shows the effect of clearance between shelling cylinder and concave (mm) on indicators studied, and that there is a significant effect and the level of 0.05%. The clearance

between shelling cylinder and concave 28 mm indicated significant superiority up on the clearance between shelling cylinder and concave 23 mm by achieving higher sheller productivity 2.474 ton/h and quality productivity 193.735 kg.h/kw, while the clearance between shelling cylinder and concave 23 mm achieved lower power consumption 11.62 kw and lower percentage of unshelled grains 2.53 %. The reason due to increasing the clearance between shelling cylinder and concave, this allowed to increase in the quantity of unshelled ears which entering between clearance shelling cylinder and concave, consequently an increasing in sheller productivity as indicated by (5,16).

**Table 1. Effect of clearance between shelling cylinder and concave (mm) on indicators studied**

clearance between shelling cylinder and concave (mm)	Sheller productivity ( $\frac{ton}{h}$ )	Quality productivity ( $\frac{kg.h}{kw}$ )	Power consumption (kw)	Percentage of unshelled grains (%)
23	2.085	179.432	11.62	2.53
28	2.474	193.735	12.77	3.27
<b>L.S.D (0.05)</b>	<b>0.048</b>	<b>3.63</b>	<b>0.181</b>	<b>0.078</b>

Table (2) shows the effect of peripheral speed of shelling cylinder on indicators studied, and that there is a significant effect and the level of 0.05%. When increasing of the peripheral speed of shelling cylinder 900 to 1100 and 1300 m/min caused an increasing sheller productivity, quality productivity and power consumption. The results showed the following: the peripheral speed of shelling cylinder 1300 m/min indicated significant superiority up on the peripheral speed of shelling cylinder 900 and 1100 m/min in achieving higher sheller productivity 3.039 ton/h, and quality productivity 205.061 kg.h/kw, the reason is the positive relationship between the speed of shelling cylinder and productivity (9), while the peripheral speed of shelling cylinder 900 m/min achieving lower power consumption 11.78 kw and lower percentage of unshelled grains 2.37 %, because increase the speed of the cylinder causes an increasing in the power required from electric motor to rotate the shelling cylinder (12,20).

**Table 2. Effect of peripheral speed of shelling cylinder on indicators studied**

peripheral speed of shelling cylinder (m/min)	Sheller productivity ( $\frac{ton}{h}$ )	Quality productivity ( $\frac{kg.h}{kw}$ )	Power consumption (kw)	Percentage of unshelled grains (%)
900	2.157	183.107	11.78	2.37
1100	2.694	197.363	13.65	2.84
1300	3.039	205.061	14.82	3.25
<b>L.S.D (0.05)</b>	<b>0.048</b>	<b>3.77</b>	<b>0.195</b>	<b>0.082</b>

The table (3) shows the interaction between the clearance between shelling cylinder and concave (mm) with peripheral speed of shelling cylinder m/min on indicators studied, and that there is a significant effect and the level of 0.05%. The interaction between the clearance between shelling cylinder and concave 28 mm with peripheral speed of shelling cylinder 1300 m/min indicated significant superiority up on the interaction between the clearance between

shelling cylinder and concave 23 mm with peripheral speed of shelling cylinder 900 m/min in achieving higher sheller productivity 3.125 ton/h, and quality productivity 218.838 kg.h/kw, while the clearance between shelling cylinder and concave 23 mm with peripheral speed of shelling cylinder 900 m/min. Indicated significant superiority up on the interaction between the clearance between shelling cylinder and concave 28 mm with peripheral speed of

shelling cylinder 1300 m/min in achieving lower power consumption 11.74 kw, and lower percentage of unshelled grains 2.62 %. The reason was due to interaction between clearance and cylinder speed, whenever the centrifugal

speed of cylinder that increased collision speed of ears with cylinder plates and sheller walls and, therefore, leads to high production value, and obtaining percentage of unshelled grains (4,10).

**Table 3. Effect the interaction between the clearance between shelling cylinder and concave (mm) with peripheral speed of shelling cylinder m/min on indicators studied**

clearance between shelling cylinder and concave (mm)	peripheral speed of shelling cylinder (m/min)	Sheller productivity ( $\frac{ton}{h}$ )	Quality productivity ( $\frac{kg \cdot h}{kw}$ )	Power consumption (kw)	Percentage of unshelled grains (%)
23	900	2.064	175.809	11.74	2.62
	1100	2.381	185.148	12.86	3.48
	1300	2.906	210.732	13.79	3.77
28	900	2.113	172.209	12.27	2.86
	1100	2.672	204.594	13.06	3.75
	1300	3.125	218.838	14.28	4.12
L.S.D (0.05)		0.049	2.85	0.163	0.091

## CONCLUSIONS:

The results showed the following:

- 1- The peripheral speed of shelling cylinder 1300 (m/min) with clearance between shelling cylinder and concave 28 (mm) led to an increasing in the sheller productivity and quality productivity.
- 2- The peripheral speed of shelling cylinder 900 (m/min) with clearance between shelling cylinder and concave 23 (mm) led to get less power consumption and Percentage of unshelled grains.

## REFERENCES:

- 1- Abhijeet, Y., Kedge, Arjun, B., Mane, Nadeem, H., Nadaf, Rahul, A. and Devarshi. 2016. A review on design of peeling-shelling compact combo machine. International Research Journal of Engineering and Technology. V.03 (Issue: 10); 1024-1027.
- 2- Adewole, C. A., T. M, Babajide, and A. M. Oke. 2015. Critical evaluation of locally fabricated maize shelling machine. International journal of engineering science and innovative technology (IJESIT) V. 4 (Issue 2); 67-73.
- 3- Akubuo, C.O. 2003. Performance evaluation of a local maize sheller. Unpublished B.Sc. Thesis; Department of Agricultural engineering, university of Nsukka.
- 4- Anirudha G. D. and C. C. Handa. 2015. Literature review of corn sheller machine. international journal for innovative research in science & technology V.2 (Issue 01); 238-240.
- 5- Aremu, D.O., Adewumi, I.O. and Ijadunola, J.A. 2015. Design, fabrication and performance evaluation of a motorized maize shelling machine. Journal of Biology, Agriculture and Healthcare. V.5, №.5; 154-164.
- 6- Dagninte, A.W., Endalew, A. Endeblihatu and S. Tekeste. 2017. Evaluation and demonstration of maize sheller for small-scale farmers. Moj applied Bionics and Biomechanics. V.1(Issue 3); 1-7.
- 7- El -Sharawy, H.M., A.H. Bahnasawy, Z.A. EL-Haddad, and M.T. Afifi. 2016. A local corn sheller performance as affected by moisture content and machine rotational. Collage of Agriculture, Benha University., Egypt, pp: 1-22.
- 8- Ghaudary, S. 2016. Development and performance evaluation of modified maize dehusker cum sheller. department of farm machinery & power engineering Vaugh school of Agriculture engineering and technology. India. Thesis. Pp:61-70.
- 9- Hussain, S. Z., and H. R. Naik., and A. H. Rather and Junaid Khan. 2009. Comparative evaluation of horizontal maize cob sheller with traditional methods of maize shelling. Gaurav Society of Agricultural Research Information Centre. V.10 №.1: 168-170.
- 10- Karikatti G., Satish J. J., Anjali K., Roopa L., and Sameer S. 2015. Crank Operated Maize Sheller. International Journal for Scientific Research & Development.3: 561-564.
- 11- Kedar P.S., Pandit, G. Pol, S. Kadam, and A. Jadhav. 2016. Design and fabrication of

corn shelling and threshing machine. International journal of innovative research in science, engineering and technology. V.5 (Issue 7); 13981-13986.

**12-** Mislaini, and Santosa and Widyawati. 2015. Study of Techno-Economic of corn sheller type MPJ-01-TEP-2014. International journal on advanced science, engineering and information technology. V.5, № 1: 23-26.

**13-** Naveenkumar, D.B., .2011. Modification and Evaluation of Power Operated Maize (zea mays l.) sheller. Department of agricultural engineering, university of Agricultural sciences Bangalore. Thesis, pp.: 27-30.

**14-** Naveenkumar, D. B. and K. S. Rajshekarappa. 2012. Performance evaluation of a power operated maize sheller. Internal. J. agric. Eng., V. 5(2): 172-177.

**15-** Oriaku, E.C., C.N. Agulanna, H.U. Nwannewuihe, M.C. Onwukwe and Adiele. 2014. Design and Performance Evaluation of a Corn De-Cobbing and Separating Machine. American Journal of Engineering Research. V.3 (Issue 06); 127-136.

**16-** Pius, B.M. 2016. Design and fabrication of an improved maize shelling machine. African journal of science, Technology, Innovation and development. V. 8 (Issue 3); 275-280.

**17-** Taha, F.J. and T.H. Alayoubi. 2012. Study some technical specifications such as sheller type and feeder speed and drying temperature affecting on nutrition value for Maize crop. Euphrates Journal of Agriculture Science.V. 3 (2): 70-76.

**18-** Tanko B. and B. J. Bature. 2017. Design, fabrication and performance evaluation of a hand operated maize sheller. Department of agricultural and environmental engineering, University of Agriculture, Makurdi, Nigeria. Researcher, V. 9(3): 39-47.

**19-** Vinay. 2014. Design and development of pedal operated maize sheller. Department of Processing and Food Engineering College of Agricultural Engineering & Technology CCS Haryana Agricultural University, Hisar. Thesis. Pp: 20- 35.

**20-** Waree, S., Somchai, C., and Khwantri S. 2016. Design factors affecting losses and power consumption of an axial flow corn shelling unit. Department of Agricultural Engineering,

Faculty of Engineering. Thailand. 38 (5), 591-598.